



Geo-Loop Inc.

Model 30-500 Two Tank

The leader in geothermal and water well grouting equipment.



(Shown with optional hose reel valve.)

Need continuous flow with huge pumping capability, volume, and pressure? Then, the **Geo-Loop 30-500 Two Tank** is the grouter for you! Featuring two 60 gallon stainless steel mixing tanks with smooth taper cone bottoms, you can easily achieve continuous 0 to 30 gallons per minute and pressures up to an astounding 500 PSI with our bulletproof two cylinder piston pump. Cycle times can be a mere one minute per batch. Sounds too good to be true? Try the **Geo-Loop 30-500 Two Tank** continuous flow system for cement, bentonite, or sand bentonite grouts and we'll make a believer out of you!

Continuous flow---Amazing speed!

Designed and built by professionals who understand *YOUR* needs.

Model 30-500 Two Tank

Features:

- 5" bore, 8" stroke piston pump with two bulletproof, chrome-lined cylinders featuring hammer union construction
- 5" standard A-style piston rubbers
- 24 HP Honda 2 cylinder electric start engine
- High capacity water fill pump and high pressure wash down line
- Tandem hydraulic pump, 3 hydraulic circuits for ease of operation
- Continuously pumps 0-30 gallons per minute and pressures up to 500 PSI
- Stainless steel paddle mixers with hinged lid covers
- Two 60 gallon stainless steel mixing tanks with smooth taper cone bottom
- 18 gallon hydraulic oil reservoir with a sight glass and thermometer
- Thermostatically controlled oil cooler with a 12 volt fan
- Tach hour meter
- Full length fork lift pockets on both ends of the framework
- Durable powder coat paint finish
- Stainless steel bag platform
- Piston pump covered by the US Patent D405-454
- 86" x 40" footprint frame
- Approximately 1,700 pounds

Options:

- Self-prime water pump
- Hose reel
- Trailer mount

Maximum theoretical performance shown. Maximum output and pressure can not be reached simultaneously. Performance will vary depending on grout, mix design, and grout line diameter and length. Specifications and products subject to change without prior notice.



If speed is your need, then the **Geo-Loop 30-500 Two Tank** is the continuous flow grouter for you. Keep everything moving with the dual 60 gallon stainless steel mixing tanks, featuring a two cylinder dependable 5" bore, 8" stroke piston pump and reliable 24 HP Honda engine. Featuring a hydraulic oil cooler and 18 gallon hydraulic oil reservoir, the system will give you the service you deserve. Clean up is easy with the high capacity water fill pump and high pressure wash down line. The entire package fits neatly on a versatile dual full-length fork lift pocket. Larger scale diesel powered units are available. Let us custom build one for you!



For more information contact Jeff Bowen at:
Geo-Loop Inc. • 316 East Ninth Street • Aurelia, Iowa 51005
Phone: 800-580-5965 • 712-434-2125 • Fax: 712-434-2115
Website: www.geo-loop.com • Email: jeff@geo-loop.com